



Proud Distributor of
Owens Corning® Products



EcoTouch® Insulation

Owens Corning® EcoTouch® Insulation is used in a wide range of ceiling, wall and floor applications. Can be installed in wood or metal framing cavities, or can be installed between furring strips.

- **Easy to Handle, Faster to Install** — made with PureFiber® Technology, it is soft to the touch and provides for fast, easy handling and installation with less dust.
- **Excellent Thermal Control** — made in R-values from 11 to 38, and thicknesses from 3½" to 12".
- **Effective Acoustical Control** — enhances interior noise control by improving the Sound Transmission Class (STC) of walls and floor/ceiling assemblies.
- **Long Term Performance** — dimensionally stable and will not slump within the wall cavity. Will not support fungi and mildew growth and is noncorrosive to steel, copper and aluminum.
- **Designed with the Environment in Mind** — contains more than 99% natural ingredients, and includes a minimum of 58% total recycled content. GREENGUARD GOLD Certified and is verified to be formaldehyde free.
- **SpaceSaver Packaging** — compression packaged in exclusive SpaceSaver packaging reduces freight and speeds job site handling/installation.



DW is an independent distributor and is not an affiliate of Owens Corning Insulating Systems, LLC or its affiliated companies.
THE PINK PANTHER™ & © 1964–2017 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2017 Owens Corning. All Rights Reserved.