



Insulation for the Envelope

Rmax Thermasheath®

This lightweight thermal insulation board has reinforced aluminum foil facers. Thermasheath® is suitable for use in:

- Stud Walls
- Cavity walls
- Masonry walls
- Exterior stucco
- Re-siding
- Vaulted ceilings
- Attics and crawls spaces
- Concrete foundations
- Limited roofing
- Exterior ducting

Rmax Thermasheath®-SI

Thermasheath®-SI is a composite product made up of energy-efficient insulation and a structural component and is designed to work seamlessly with non-structural Rmax Thermasheath® on:

- Stud walls
- Brick veneer
- Stone
- Stucco
- Wood
- Vinyl siding
- Aluminum siding
- Cement board siding

DW SKU	X-REF	DESCRIPTION	ARL	RR	OKC
RM4812SI	A1K0	THERMASHEATH SI 4' X 8' X 1/2" 80 PCS PER UNIT	✓		
RM4812T3	A1K1	THERMASHEATH T3 4' X 8' X 1/2", 48 PCS PER UNIT	✓	✓	
RM4834T3	A1K2	THERMASHEATH T3 4' X 8' X 3/4" 30 PCS PER UNIT	✓	✓	
RM4912SI	A1K3	THERMASHEATH SI 4' X 9' - 1/2"	✓		
RMCTAPE	A1K5	CONSTRUCTION TAPE - 3" X 165' ROLL, 16 ROLL/CASE	✓		