



Timberline[®] HDZ[™]
High Definition[®] Lifetime Shingles



Accuracy Made Easy

StrikeZone[™] Nailing Area

1.81" – the industry's widest nailing area. Nails penetrate the shingle below for secondary fastening. Our legendary Dura Grip[™] sealant pairs with the smooth microgranule surface of the StrikeZone nailing area for fast tack.

Exclusive LayerLock[™] Technology

mechanically fastens the common bond, allowing for a larger nailing area.

Faster Application

In an independent research study, Timberline[®] HDZ[™] Shingles were fastened to the roof deck with 30% faster nail fastening vs. GAF standard architectural shingles



X-REF#	DW SKU	DESCRIPTION
A9H7	PTHDBW	GAF Timberline HDZ Laminate Barkwood SG
A9H8	PTHDC	GAF Timberline HDZ Laminate Charcoal SG
A9H9	PTHDI	GAF Timberline HDZ Laminate Hickory SG
A0I0	PTHDMB	GAF Timberline HDZ Laminate Mission Brown SG
A0I1	PTHDPG	GAF Timberline HDZ Laminate Pewter Grey SG
A0I2	PTHDSHW	GAF Timberline HDZ Laminate Shakedown SG
A0I3	PTHDSL	GAF Timberline HDZ Laminate Slate SG
A0I4	PTHDWW	GAF Timberline HDZ Laminate Weathered Wood SG

No-Max Wind Speed Limit Wind Warranty

Must use GAF H-R, ProStart, Synthetic Underlayment, and **either** GAF Leak Barrier **or** Ventilation. Four (4) components total.